NA to CYS EN 1994-2:2005 (Including AC:2009)

NATIONAL ANNEX TO CYS EN 1994-2:2005 (Including Corrigendum AC:2009)

Eurocode 4: Design of composite steel and concrete structures

Part 2: General rules and rules for bridges



NATIONAL ANNEX

TO

CYS EN 1994-2:2005 (Including Corrigendum AC:2009)
Eurocode 4: Design of composite steel and concrete
structures

Part 2: General rules and rules for bridges

This National Annex has been approved by the Board of Directors of the Cyprus Organisation for Standardisation (CYS) on 14.06.2019.

Copyright

Right to reproduce and distribute belongs to the Cyprus Organisation for Standardisation.

No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying, without permission in writing from Cyprus Organisation for Standardisation.

If you have any questions about standards copyright, please contact Centre of Information and Customer Service at the Cyprus Organisation for Standardisation phone: +357 22 411413/4 email: c.service@cys.org.cy

National Annex to CYS EN 1994-2:2005 (including Corrigendum AC:2009) Eurocode 4: Design of Composite Steel and Concrete Structures Part 2: General Rules and Rules for Bridges

INTRODUCTION

This National Annex has been prepared by the CYS TC 18 National Standardisation Technical Committee of Cyprus Organisation for Standardisation. (CYS)

NA 1 SCOPE

This National Annex is to be used together with CYS EN 1994-2:2005(including Corrigendum AC:2009). Any reference in the rest of text to CYS EN 1994-1:2004 means the above document.

This National Annex gives:

- (a) Nationally determined parameters for the following clauses of CYS EN 1994-2:2005 where National choice is allowed (see Section NA 2)
 - 1.1.3 (3)
 - 2.4.1.1(1)
 - 2.4.1.2 (5)P
 - 2.4.1.2 (6) P
 - 5.4.4 (1)
 - 6.2.1.5 (9)
 - 6.2.2.5 (3)
 - 6.3.1 (1)
 - 6.6.1.1 (13)
 - 6.6.3.1 (1)
 - 6.8.1 (3)
 - 6.8.2 (1)
 - 7.4.1 (4)
 - 7.4.1. (6)
 - 8.4.3 (3)
- (b) Decision on the use of the Informative Annex C (see Section NA 3)
- (c) References to non-contradictory complementary information to assist the user to apply CYS EN 1994-2:2005. In this National Annex such information is provided for the following clauses in CYS EN 1994-2:2005 (see Section NA 4)

NA 2 NATIONALLY DETERMINED PARAMETERS

NA 2.1 Clause 1.1.3 (3) Scope of Part 2 of Eurocode 4

No other guidance for shear connectors is provided.

NA 2.2 Clause 2.4.1.1 (1) Design values of actions

The value defined for symbol γ_P is set to 1,0 both for favourable and unfavourable effects.

NA 2.3 Clause 2.4.1.2 (5)P Design values of material or product properties The value defined for symbol γv is set to 1,25.


NA 2.4 Clause 2.4.1.2 (6)P Design values of material or product properties

The value defined for symbol $\gamma_{Mf,s}$ is set to 1,0

CYS TC 18 Page 2 of 4

NA 2.5 Clause 5.4.4 (1) Combination of global and local action effects

The values defined for the combination factor ψ , are shown in Figure E.2 of Annex E of EN 1993-2.



NA 2.6 Clause 6.2.1.5 (9) Elastic resistance to bending

Methods (7) and (8) or Section 10 of EN 1993-1-5 may be used.

NA 2.7 Clause 6.2.2.5 (3) Additional rules for beams in bridges

The values defined for symbols $C_{\text{Rd,c}}$ is set to 0,15/ γ_{C} , k_{1} is set to 0,12 and $\sigma_{\text{cp,0}}$ is set to 1,85N/mm².

NA 2.8 Clause 6.3.1 (1) Filler beam decks - Scope

No further reference for transverse filler beams is provided.

NA 2.9 Clause 6.6.1.1 (13) Shear connection – Basis of design

No further guidance is provided.

NA 2.10 Clause 6.6.3.1 (1) Headed stud connectors – Design Resistance

The value defined for symbol γv is set to 1,25.

NA 2.11 Clause 6.8.1 (3) Fatigue – General

The value defined for symbol k_s is set to 0,75.

NA 2.12 Clause 6.8.2 (1) Partial factors for fatigue assessment of bridges

The value defined for symbol of $\gamma_{Mf,s}$ is set to 1,0..

NA 2.13 Clause 7.4.1 (4) Cracking of concrete – General

The values defined for symbol w_k is set to w_{max} found in the Note to EN 1992-2, 7.3.1 (105).

NA 2.14 Clause 7.4.1 (6) Cracking of concrete – General

The recommended temperature difference 20K is adopted.

NA 2.15 Clause 8.4.3 (3)

No further information is provided.

CYS TC 18 Page 3 of 4

National Annex to CYS EN 1994-2:2005 (including Corrigendum AC:2009) Eurocode 4: Design of Composite Steel and Concrete Structures Part 2: General Rules and Rules for Bridges

NA 3 DECISION ON USE OF THE INFORMATIVE ANNEX C

NA 3.1 Annex C

Annex C may be used.

NA 4 REFERENCES TO NON-CONTRADICTORY COMPLEMENTARY INFORMATION

None

CYS TC 18 Page 4 of 4



NA to CYS EN 1994-2:2005 (Including AC:2009)

CYPRUS ORGANISATION FOR STANDARDISATION

Limassol Avenue and Kosta Anaxagora 30, 2nd & 3rd Floor, 2014 Strovolos, Cyprus P.O.BOX.16197, 2086 Nicosia, Cyprus

Tel: +357 22 411411 Fax: +357 22 411511

E-Mail: cystandards@cys.org.cy
Website: www.cys.org.cy